



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

Neutron Skyshine Considerations For The NIF Shielding Design

M. S. Singh, J. M. Mecozzi, M. T. Tobin

February 5, 2004

49th Annual Meeting of the Health Physics Society
Washington, DC, United States
July 11, 2004 through July 15, 2004

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

NEUTRON SKYSHINE CONSIDERATIONS FOR THE NIF SHIELDING DESIGN*

M. S. Singh, J. M. Mecozzi and M. T. Tobin (Lawrence Livermore National Laboratory, Box 808, Livermore, CA, 94550)UCRL-CONF-202214

A series of coupled neutron-photon transport Monte-Carlo calculations was performed to estimate the roof shielding required to limit the skyshine dose to less than 1 mrem/y at the site boundary when conducting DT experiments with annual fusion yields up to 1200 MJ (4.2×10^{20} neutrons/y). The NIF shielding design consists of many different components. The basic components include 10-cm-thick Al chamber with 40-cm-thick target chamber gunite shield having multiple penetrations, 1.83-m-thick concrete Target Bay walls, 1.37-m-thick concrete roof, and multiple concrete floors with numerous penetrations. Under this shielding configuration, the skyshine dose at the nearest site-boundary was calculated to be less than 0.2 mrem/y for all possible target illumination configurations. The potential dose at the site boundary would be about one-tenth of the cosmic neutron dose that we measured with bubble neutron detectors on board a commercial roundtrip flight from SF to Rochester. This incremental dose increase is well within the normal fluctuations (noise) of the natural background radiation in the Livermore area. The skyshine dose has no impact on the public. The skyshine dose trends at ground and elevated levels are plotted as a function of distance from 20 m to 1000 m from the center of the target bay. The differential neutron and photon energy flux emerging from the NIF roof and at several locations on the ground is plotted to show how it shifts with distance. The results of this study are compared with the neutron skyshine studies done at high-energy accelerators by R. H. Thomas. *(This work was performed under the auspices of the U. S. Department of Energy by the University of California, Lawrence Livermore National Laboratory under Contract No. W-7405-Eng-48.)

Submitted for presentation at the 49th Annual Meeting of the Health Physics Society, July 11-15, Washington, DC